

## STANDARD CONFIGURATION CATALOG PAGE

This document is an addendum to the M4067 Series datasheet, detailing the specific features and parameters of this variant of the M4067 Series power supplies.

**SERIES: M4067**

**CONFIGURATION: M4067-103**

### ***ELECTRICAL SPECIFICATIONS:***

Input	Outputs					
	VS1	VS2	VS3	+12_Aux	-12_Aux	3.3_Aux
103-127V <sub>AC</sub> 400Hz Triple-Phase	12V/35A	12V/35A	5V/40A	12V/1A	-12V/1A	3.3V/15A

### ***SPECIAL FEATURES:***

- Max Total Output Power: 1140W
- No Current-Sharing
- IPMI Communication

*Note: Specifications are subject to change without prior notice by the manufacturer.*



**Cham, Switzerland**  
[www.enercon-europe.com](http://www.enercon-europe.com)  
[enercon@enercon-europe.com](mailto:enercon@enercon-europe.com)  
 +41-41-740-4554

#### Global Headquarters

**Netanya, Israel**  
[www.enercon.co.il](http://www.enercon.co.il)  
[sales@enercon.co.il](mailto:sales@enercon.co.il)  
 +972-73-246 9200



**Gurgaon, India**  
[www.mpsindia.in](http://www.mpsindia.in)  
[sales@mpsindia.in](mailto:sales@mpsindia.in)  
 +91-124-651 0010