

## STANDARD CONFIGURATION CATALOG PAGE

This document is an addendum to the M4701 Series datasheet, detailing the specific features and parameters of this variant of the M4701 Series power supplies.

**SERIES: M4701**

**CONFIGURATION: M4701-100**

### *ELECTRICAL SPECIFICATIONS:*

Input	Outputs			
	PO1, PO2, PO3	3.3V_Aux	12V_Aux	-12V_Aux
103-127 V <sub>AC</sub> 400 Hz three-phase	12V/100A	3.3V/30A	N/A	N/A

### *SPECIAL FEATURES:*

- 46.11 System Management Protocol
- 12V Active-current share
- 3.3V Active-current share



**Cham, Switzerland**  
[www.enercon-europe.com](http://www.enercon-europe.com)  
[sales@enercon-europe.com](mailto:sales@enercon-europe.com)  
 +41-41-740-4554

#### Global Headquarters

**Netanya, Israel**  
[www.enercon.co.il](http://www.enercon.co.il)  
[sales@enercon.co.il](mailto:sales@enercon.co.il)  
 +972-73-246 9200



**Gurgaon, India**  
[www.mpsindia.in](http://www.mpsindia.in)  
[sales@mpsindia.in](mailto:sales@mpsindia.in)  
 +91-124-651 0010